

# Safety Data Sheet

According To Regulation (EC) No 1907/2006 (REACH)

## PROMAST PREMIUM SAFETY VALVE FOAM

Version:1.0

Preparation Date:9.21.2023

Form No:41039-EN

Revision Date: 9.21.2023

### 1. IDENTIFICATION OF THE PRODUCT AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product Identifier

**Product Name** Promast Premium Safety Valve Foam

**SDS No:** 41039-EN

#### 1.2 Relevant Identified Uses Of The Product And Uses Advised Against

Filling and fixing.

#### 1.3 Details Of The Supplier Of The Safety Data Sheet

**Supplier :** PROMAST KIMYA SAN. TİC. A.Ş.

**Address – Factory:** Ovacık Mah. Hacıoğlu Sok. No:21B Kullar Mevkii 41140  
Başiskele- Kocaeli/Türkiye  
Tel: +90 262 335 41 82

**Information Providing  
Authority About Safety  
Data Sheet** info@promast.com.tr

#### 1.4 Emergency Telephone Number

**Company Emergency:** +90 262 335 41 82

### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification Of The Product

##### 2.1.1 Classification According to Regulation (EC) No 1272/2008

-Extremely flammable gas; H222

-Pressurised container; H229

-Skin Irrit. Cat 2; H315

-Eye Irrit. Cat 2; H319

-Resp. Sens. Cat 1; H334

-Skin Sens. Cat.1; H317

-Car. Cat 2; H351

-STOT SE. Cat 3; H335

-STOT RE. Cat 2; H373

-Rep. Tox. ; H362

-Aquatic Acute, Cat 1; H400

# Safety Data Sheet

According To Regulation (EC) No 1907/2006 (REACH)

## **PROMAST PREMIUM SAFETY VALVE FOAM**

Version:1.0

Preparation Date:9.21.2023

Form No:41039-EN

Revision Date: 9.21.2023

-Aquatic Chr., Cat.1- H410

### 2.2 Label Elements

#### 2.2.1. Labeling According to Regulation (EC) No 1272/2008 [CLP<sub>1</sub>/GHS<sub>2</sub>]

##### Product Identifier

##### Hazard Component for Labelling

- 4-4'-methylenediphenyl diisocyanate
- Polyol Blend

##### Hazard Pictograms



##### Signal Word

- Danger

##### Hazard Statements

- H222 Extremely flammable aerosol.
- H229 Pressurised container; may burst if heated.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H362 May cause harm to breast-fed children.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

##### Precautionary Statements

- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211: Do not spray on an open flame or other ignition source.

## Safety Data Sheet

According To Regulation (EC) No 1907/2006 (REACH)

### **PROMAST PREMIUM SAFETY VALVE FOAM**

Version:1.0

Preparation Date:9.21.2023

Form No:41039-EN

Revision Date: 9.21.2023

- P251: Do not pierce or burn, even after use.*
- P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F*
- P264: Wash contaminated skin thoroughly after handling.*
- P263: Avoid contact during pregnancy/while nursing.*
- P280: Wear protective gloves/ protective clothing/ eye protection/ face protection.*
- P281: Use personal protective equipment as required.*
- P308+P313: IF exposed or concerned: Get medical advice/attention.*
- P405: Store locked up.*
- P273: Avoid release to the environment.*
- P391: Collect spillage.*
- P302+P352: IF ON SKIN: wash with plenty of water.*
- P321: Specific treatment (see on this label).*
- P362: Take off contaminated clothing.*
- P261: Avoid breathing dust/fume/gas/mist/vapours/spray.*
- P260: Do not breathe dust/fume/gas/mist/vapours/spray.*
- P272: Contaminated work clothing should not be allowed out of the workplace.*
- P270: Do not eat, drink or smoke when using this product.*
- P333+P313: IF SKIN irritation or rash occurs: Get medical advice/ attention.*
- P363: Wash contaminated clothing before reuse.*
- P501: Dispose of contents/container to the local regulations.*
- P337+P313: If eye irritation persists: Get medical advice/attention.*
- P285: In case of inadequate ventilation wear respiratory protection.*
- P304+P341: If INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.*
- P342+P311: If experiencing respiratory symptoms: Call a POSITION CENTER/DOCTOR*
- P201: Obtain special instructions before use.*
- P202:Do not handle until all safety precautions have been read and understood.*
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*

# Safety Data Sheet

According To Regulation (EC) No 1907/2006 (REACH)

## PROMAST PREMIUM SAFETY VALVE FOAM

Version:1.0

Preparation Date:9.21.2023

Form No:41039-EN

Revision Date: 9.21.2023

P314: Get medical attention/advice if you feel unwell.

### Supplemental Hazard Information (EU) Statements

EUH204 Contains isocyanates. May produce an allergic reaction.

### 2.3 Additional Labeling

Not data available.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Description Of The Mixture:

Ingredient name	EC number	CAS number	% w/w	Hazard statement
Propane	200-827-9	74-98-6	1-5	Flam. Gas 1- H220
Polyol Blend	-	-	30-50	Aquatic Acute 1- H400 Aquatic Chr.1- H410 Rep. Tox.- H362
Butane	203-448-7	106-97-8	1-5	Flam. Gas 1-H220
Isobutane	200-857-2	75-28-5	1-5	Flam. Gas 1- H220
Dimethyl ether	204—065-8	115-10-6	5-10	Flam. Gas 1- H220
4-4'-methylenediphenyl diisocyanate	202-966-0	101-68-8	15-25	Carc. 2 - H351 Acute Tox. 4 - H332 STOT RE 2 - H373 Eye Irrit. 2 - H319 STOT SE 3 - H335 Skin Irrit. 2 - H315 Resp. Sens. 1 - H334 Skin Sens. 1 - H317

#### 3.1.1 Notes

None

#### 3.1.2 Additional information:

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 4. FIRST AID MEASURES

# Safety Data Sheet

According To Regulation (EC) No 1907/2006 (REACH)

## **PROMAST PREMIUM SAFETY VALVE FOAM**

Version:1.0

Preparation Date:9.21.2023

Form No:41039-EN

Revision Date: 9.21.2023

### **4.1 Description of first aid measures**

#### **4.1.1 General information**

Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

#### **4.1.2 Following inhalation**

In case of inhalation of spray mist: Move person into fresh air and keep at rest. Provide rest, warmth and fresh air. Get medical attention if any discomfort continues.

#### **4.1.3 Following skin contact**

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

#### **4.1.4 Following eye contact**

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

#### **4.1.5 Following ingestion**

Immediately rinse mouth and provide fresh air. Get medical attention if any discomfort continues.

### **4.2 Most important symptoms and effects, both acute and delayed**

#### **Inhalation**

Dizziness. Allergy or asthma symptoms or breathing difficulties.

#### **Ingestion**

Nausea, vomiting.

#### **Skin contact**

May cause an allergic skin reaction. Causes irritation.

#### **Eye contact**

Causes eye irritation.

### **4.3 Notes for the doctor**

Treat symptomatically.

## **5. FIRE-FIGHTING MEASURES**

### **5.1 General Information and Flammable Properties:**

**Extinguishing media:** Water spray, dry chemical powder, carbon dioxide

**Unsuitable extinguishing media:** Do not use water jet.

### **5.2 Special hazards arising from the product**

# Safety Data Sheet

According To Regulation (EC) No 1907/2006 (REACH)

## **PROMAST PREMIUM SAFETY VALVE FOAM**

Version:1.0

Preparation Date:9.21.2023

Form No:41039-EN

Revision Date: 9.21.2023

Vapours may form explosive mixtures with air. Aerosol cans may explode in fire. In case of fire, toxic gases may be formed. Carbon monoxide, carbon dioxide.

### **5.3 Advice for fire-fighters:**

#### **Fire Fighting Instructions**

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours. Avoid breathing fire vapours. Move container from fire area if it can be done without risk. Be aware of danger for fire to restart. Dike and collect extinguishing water.

#### **Protective Equipment For Fire-Fighting Personnel**

Face mask, protective gloves and safety helmet. Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## **6. ACCIDENTAL RELEASE MEASURES**

### **6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material.

### **6.2 Environmental Precautions**

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### **6.3 Methods and Material For Containment and Cleaning Up**

#### **6.3.1 For Containment**

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

#### **6.3.2 For Cleaning Up**

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Small Spillages: Collect spillage. Large Spillages: Absorb spillage with non-combustible, absorbent material. The contaminated absorbent may pose the same hazard as the spilled material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush

# Safety Data Sheet

According To Regulation (EC) No 1907/2006 (REACH)

## PROMAST PREMIUM SAFETY VALVE FOAM

Version:1.0

Preparation Date:9.21.2023

Form No:41039-EN

Revision Date: 9.21.2023

contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

### 7. HANDLING AND STORAGE

#### 7.1 Precautions For Safe Handling

Read and follow manufacturer's recommendations. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid breathing vapour or mist. Avoid breathing gas.

Do not pierce or burn, even after use. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Empty containers retain product residue and can be hazardous.

Store and use away from heat, sparks, open flame or any other ignition source. Use explosionproof electrical (ventilating, lighting and material handling) equipment. Use only nonsparking tools. Keep away from ignition sources such as heat/sparks/open flame. No smoking. Do not spray on a naked flame or any incandescent material. Product contaminated rags, paper or material used to absorb spillages, represent a fire hazard, and should not be allowed to accumulate. Dispose of safely immediately after use.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas

#### 7.2 Conditions For Safe Storage, Including Any Incompatibilities

##### Storage conditions

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Protect against physical damage and/or friction. Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry and cool place.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control Parameters

Name	STD	TWA – 8 Hrs		STEL – 15 Min		Notes
Butane	WEL	600 ppm	1450 mg/m <sup>3</sup>	750 ppm	1810 mg/m <sup>3</sup>	-
Propane	WEL	1000 ppm	1800 mg/m <sup>3</sup>	---	2.8 mg/m <sup>3</sup>	-
DIPHENYLMETHANE-4,4'-DI-ISOCYANATE	WEL	---	0.02 mg/m <sup>3</sup>	---	0.07 mg/m <sup>3</sup>	
DIMETHYL ETHER	WEL	400 ppm	766 mg/m <sup>3</sup>	500 ppm	958 mg/m <sup>3</sup>	-

# Safety Data Sheet

According To Regulation (EC) No 1907/2006 (REACH)

## PROMAST PREMIUM SAFETY VALVE FOAM

Version:1.0

Preparation Date:9.21.2023

Form No:41039-EN

Revision Date: 9.21.2023

### 8.2 Occupational Exposure Limits



#### 8.2.1 Appropriate Engineering Controls

#### 8.2.2 Personal Protection Equipment

##### Eye/Face Protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

##### Skin Protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

##### Hand Protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

##### Respiratory Protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.



## Safety Data Sheet

According To Regulation (EC) No 1907/2006 (REACH)

### PROMAST PREMIUM SAFETY VALVE FOAM

Version:1.0

Preparation Date:9.21.2023

Form No:41039-EN

Revision Date: 9.21.2023

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

##### 9.1 Appearance

Appearance:	Aerosol foam
Color:	White
Odour:	No data available
pH:	No data available
Melting Point / Freezing Point (°C) 760 mmHg	No data available
Boiling point/range(°C):	No data available
Vapour pressure Pa(<1.00x10 <sup>-10</sup> mmHg)@ 20°C:	No data available
Relative Density kg/m <sup>3</sup> @25°C :	23-26
Flash Point °C:	No data available
Flame Point °C:	No data available
Flammability:	B3
Vapor Density (Air=1):	No data available
Vaporization rate:	No data available
Solidification point/range, °C:	No data available
Solubility	No data available
Explosive Property:	No data available
Oxidation Property:	No data available

##### 9.2 Other Information

Viscosity 22 °C (s61 spindle):	No data available
Adhesion Time:	No data available

#### 10. STABILITY AND REACTIVITY

##### 10.1 Reactivity

*There are no known reactivity hazards associated with this product.*

##### 10.2 Chemical Stability

*Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.*

##### 10.3 Possibility of Hazardous Reactions

*Unkown*

##### 10.4 Conditions to Avoid

*Avoid heat, flames and other sources of ignition. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.*

##### 10.5 Incompatible Materials

## Safety Data Sheet

According To Regulation (EC) No 1907/2006 (REACH)

### **PROMAST PREMIUM SAFETY VALVE FOAM**

Version:1.0

Preparation Date:9.21.2023

Form No:41039-EN

Revision Date: 9.21.2023

*Strong oxides*

#### **10.6 Hazardous Decomposition Products**

**Fire creates:** Toxic Gasses / vapors / fumes of: Ammonia or Amines. Carbon Monoxides (CO). Oxides of: Nitrogen, Hydrogen Cyanide (HCN), Nitrous Gases (Nox).

### **11. TOXICOLOGICAL INFORMATION**

#### **11.1 General Information**

*No data available.*

#### **Acute Toxicity**

*Harmfull if swallowed and inhaled.*

#### **Skin Corrosion/Irritation**

*Causes skin irritation.*

#### **Eye Damage/Irritation**

*Causes serious eye irritation.*

#### **Respiratory or Skin Sensitization**

*May cause allergy or asthma symptoms or breathing difficulties if inhaled.*

*May cause an allergic skin reaction.*

#### **Germ Cell Mutagenicity**

*Based on available data the classification criteria are not met.*

#### **Carcinogenicity**

*Suspected of causing cancer.*

#### **Reproductive Toxicity**

*May cause harm to breast-fed children.*

#### **Specific Target Organ Toxicity- Single Exposure**

*May cause respiratory irritation.*

#### **Specific Target Organ Toxicity- Repeated Exposure**

*May cause damage to organs through prolonged or repeated exposure.*

#### **Aspiration Hazard**

*No data available.*

**Inhalation** Vapours may irritate throat and respiratory system and cause headache, dizziness and dullness.

**Ingestion** May cause nausea, headache, dizziness and intoxication.

# Safety Data Sheet

According To Regulation (EC) No 1907/2006 (REACH)

## PROMAST PREMIUM SAFETY VALVE FOAM

Version: 1.0

Preparation Date: 9.21.2023

Form No: 41039-EN

Revision Date: 9.21.2023

### 12. ECOLOGICAL INFORMATION

#### 12.1 Ecotoxicity

The product component are classified as environmentally hazardous. Spills may have hazardous effects on the environment.

#### 12.2 Photo Degradation

No data available.

#### 12.3 Biaccumulation Potential:

**Biological environment (biota) accumulation potential:** No data available.

**Potential – nutrients pass through:** No data available.

**Reference Values – Log Kow, Sw and BCF:** No data available.

#### 12.4 Mobility:

The product is not soluble in water.

#### 12.5 Results of PBT and vPvB Assesment:

No data available.

#### 12.6 Effects on Waste Water Treatment Plants

No data available.

#### 12.7 Persistence and Degradability

No data available.

### 13. DISPOSAL CONSIDERATIONS

#### 13.1 General Information

The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

### 14. TRANSPORT INFORMATION

	ADR <sup>12</sup> /RID <sup>13</sup>	ADNR <sup>14</sup>	IMDG <sup>15</sup>	ICAO <sup>16</sup> /IATA <sup>17</sup>
<b>TRANSPORTATION</b>	Road	River	Marine	Airways
<b>14.1. UN NUMBER</b>	1950	1950	1950	1950

# Safety Data Sheet

According To Regulation (EC) No 1907/2006 (REACH)





## PROMAST PREMIUM SAFETY VALVE FOAM

Version:1.0

Preparation Date:9.21.2023

Form No:41039-EN

Revision Date: 9.21.2023

14.2. PROPER SHIPPING NAME	AEROSOLS			
SYMBOL				
14.3. PACKAGING GROUP	Not applicable			
LABELLING NO	2.1	2.1	2.1	2.1
TUNNEL RESTRICTION CODE	(D)	-	-	-
EmS	F-D,S-U	-	-	-
14.5. MARINE POLLUTANT	-	-	-	-
14.6. SPECIAL PRECAUTIONS FOR THE USER	-			

## 15. REGULATORY INFORMATION

### 15.1 Chemical Safety Assesment

#### 15.1.1 Hazard

The Safety Data Sheet is compiled according to the current European requirements. Regulation

(EC) No 1907/2006 (REACH)

CLP classification according to Annex VI of CLP (Regulation (EC) No 1272/2008)

This substance is classified as not hazardous according to regulation (EC) 1272/2008

### 15.2 International Regulations

This safety data sheet complies with the requirements of Regulation (EC) No. 1272/2008/EC and 11014:2009.

## 16. OTHER INFORMATION

### 16.1 Other Information

For additional information regarding **Promast** products please contact the **PROMAST Kimya San. Tic. A.Ş** Pelin KAHRAMAN- [pelin.kahraman@urban.com.tr](mailto:pelin.kahraman@urban.com.tr)

In all cases of potential poisoning supportive therapy is of the it most importance.

### 16.2 Related Person

Prepared by: Pelin KAHRAMAN ([pelin@urbantmgd.com.tr](mailto:pelin@urbantmgd.com.tr))

Uzman Akreditasyonu No: TÜRKAK KDU 01.11.06 / 14.12.2019-14.12.2024

0216 365 64 16

#### 16.2.1 Contact Person

Mete Atakan AKMAN – [mete.akman@sls.com.tr](mailto:mete.akman@sls.com.tr)

## Safety Data Sheet

According To Regulation (EC) No 1907/2006 (REACH)

### **PROMAST PREMIUM SAFETY VALVE FOAM**

Version:1.0

Preparation Date:9.21.2023

Form No:41039-EN

Revision Date: 9.21.2023

#### **16.3 Revision Date**

09.21.2023

#### **16.4 SDS No**

41039-EN

#### **16.5 Revision Version**

1.0

#### **16.6 Reason of re-issue**

Compiling according to Regulation (EC) No 1272/2008

#### **16.7 Relevant H- and EUH-phrases(number and full text)**

##### **Hazard Statements**

H222 Extremely flammable aerosol.

H229 Pressurised container; may burst if heated.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H362 May cause harm to breast-fed children.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

##### **Precautionary Statements**

P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F

P264: Wash contaminated skin thoroughly after handling.

P263: Avoid contact during pregnancy/while nursing.

## Safety Data Sheet

According To Regulation (EC) No 1907/2006 (REACH)

### **PROMAST PREMIUM SAFETY VALVE FOAM**

Version:1.0

Preparation Date:9.21.2023

Form No:41039-EN

Revision Date: 9.21.2023

*P280: Wear protective gloves/ protective clothing/ eye protection/ face protection.*

*P281: Use personal protective equipment as required.*

*P308+P313: IF exposed or concerned: Get medical advice/attention.*

*P405: Store locked up.*

*P273: Avoid release to the environment.*

*P391: Collect spillage.*

*P302+P352: IF ON SKIN: wash with plenty of water.*

*P321: Specific treatment (see on this label).*

*P362: Take off contaminated clothing.*

*P261: Avoid breathing dust/fume/gas/mist/vapours/spray.*

*P260: Do not breathe dust/fume/gas/mist/vapours/spray.*

*P272: Contaminated work clothing should not be allowed out of the workplace.*

*P270: Do not eat, drink or smoke when using this product.*

*P333+P313: IF SKIN irritation or rash occurs: Get medical advice/ attention.*

*P363: Wash contaminated clothing before reuse.*

*P501: Dispose of contents/container to the local regulations.*

*P337+P313: If eye irritation persists: Get medical advice/attention.*

*P285: In case of inadequate ventilation wear respiratory protection.*

*P304+P341: If INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.*

*P342+P311: If experiencing respiratory symptoms: Call a POSITION CENTER/DOCTOR*

*P201: Obtain special instructions before use.*

*P202:Do not handle until all safety precautions have been read and understood.*

*P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*

*P314: Get medical attention/advice if you feel unwell.*

#### **16.8 Legal Disclaimer**

- The purpose of the above information is to describe the products only in terms of health and safety requirements.
- The information given should not, therefore, be construed as guaranteeing specific properties or as specification.

## Safety Data Sheet

According To Regulation (EC) No 1907/2006 (REACH)

### **PROMAST PREMIUM SAFETY VALVE FOAM**

Version:1.0

Preparation Date:9.21.2023

Form No:41039-EN

Revision Date: 9.21.2023

- Customers should satisfy themselves as to the suitability and completeness of such information for their own particular use.
- The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication.
- The above information relates only to the specific material(s) designated herein and may not be valid for such material(s) used in combination with any other materials or in any process or if the material is altered or processed, unless specified in the text.
- The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Due to the many factors outside our control when using this product, we cannot accept liability for any injury, accident, loss or damage caused through its use.

<sup>1</sup> SDS: Safety Data Sheet

<sup>2</sup> CLP: Classification, Labelling and Packaging of Substances and Mixtures

<sup>3</sup> GHS: Global Harmonised System

<sup>4</sup> NIOSH: The National Institute for Occupational Safety and Health

<sup>5</sup> CEN: Comite Europeen de Normalisation

<sup>6</sup> NTP: National Toxicology Program

<sup>7</sup> IARC: The International Agency for Research on Cancer

<sup>8</sup> OSHA : Occupational Safety and Health Association

<sup>9</sup> EWC : European Waste Katalog

<sup>10</sup> ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

<sup>11</sup> RID: Regulations Concerning the International Transport of Dangerous Goods by Rail

<sup>12</sup> ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways

<sup>13</sup> IMDG: International Maritime Code for Dangerous Goods

<sup>14</sup> ICAO: International Civil Aviation Organization

<sup>15</sup> IATA: International Air Transport Association

<sup>16</sup> TWA: Time Weighted Average

<sup>17</sup> PEL: Permissible Exposure Limit

<sup>18</sup> PNEC: Predicted No Effect Concentration

<sup>19</sup> OEL: Occupational exposure limit