

TECHNICAL DATA SHEET

Rust Remover



Anti Corrosive

It can be used on metal surfaces corroded by rust due to water and humidity. Cleans dust and oil on metal surfaces. Protects against moisture. After use, it forms a thin film on the surface and delays rusting.

TECHNICAL DATA

■ Type	Aerosol Spray
■ Color	Translucent
■ Odor	Characteristic
■ Flash Point (°C) (min)	<0°C
■ Density	0,759 g/cm³

APPLICATIONS AREAS

Automotive, industry, marine, household appliances, nuts and bolts, door and cabinet hinges.

APPLICATION METHODS

Shake the can before use and spray to the desired area from a 10-20 cm distance. Wait 2-3 minutes for it to take effect. Repeat the process several times in very rusty areas.

HAZARD PHRASES

- H222:Extremely flammable material.
- H229:Pressurized container. May burst if heated.
- H315:Causes skin irritation.
- H336: May cause drowsiness or dizziness.
- H361:Suspected of damaging fertility or the unborn child.
- H373:May cause damage to organs through prolonged or repeated exposure cause the hazard. H411:Toxic to aquatic life with long lasting effects.
- P210:Keep away from heat/ sparks/ open flames/ hot surfaces.
- P211:Do not spray on an open flame or other ignition source.
- P251:Pressurized container. Do not pierce or burn, even after use.
- P260:Avoid breathing dust/ smoke/ gas/ mist/ vapor/ spray.
- P280:Wear protective gloves and clothing, eye&face protection.
- P302+P352 IF CONTACTED WITH SKIN: Wash well with soap and water.
- P304+P340 IF INHALED: remove the person to fresh air.
- P410+P412: Protect from direct sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501:Dispose the container according to regulations.

DIRECTIONS FOR USE

1. Provide adequate ventilation.
2. Shake can thoroughly before use. Note: There is no ball agitator inside the can. For best results, aerosol can should be at room temperature before spraying.
3. Holding can 8 to 10 inches from the surface for open area lubrication, or 5 inches using the extension tube provided for hard to reach areas, press the nozzle and discharge the product on the assembly.

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8C to 21C unless otherwise labeled. Optimal storage is at the lower half of this temperature range.

PACKAGING (Volume)

400 ml Aerosol Can (box of 24 pieces)

